

In re Patent Application of
LEONOV

Serial No. 10/728,691

Filed: DECEMBER 5, 2003

BEST AVAILABLE COPY

In the Claims:

This listing of claims replaces all prior versions and listing of claims in the application.

Claims 1-11 (Canceled).

12. (Original) A counteracting magnetic field generator for a power generator comprising a rotor and a stator surrounding the rotor and having opposing ends, the stator comprising a stator core and a plurality of windings carried by the stator core creating an undesired axial magnetic field component adjacent the opposing ends of the stator, the counteracting magnetic field generator generating a counteracting magnetic field for counteracting the undesired axial magnetic field component at at least one end of the stator and comprising:

a first electrically conductive coil portion positioned for having an electrical current induced therein by the rotor; and

a second electrically conductive coil portion positioned adjacent the at least one end of the stator and connected to said first electrically conductive coil portion to receive the electrical current therefrom to generate the counteracting magnetic field.

13. (Original) A counteracting magnetic field generator according to Claim 12 wherein the stator is spaced from the rotor to define a gap therebetween; and wherein said

In re Patent Application of
LEONOV
Serial No. 10/728,691
Filed: DECEMBER 5, 2003

BEST AVAILABLE COPY

first electrically conductive coil portion is positioned in the gap.

14. (Original) A counteracting magnetic field generator according to Claim 12 wherein the stator core includes a recess therein receiving said first electrically conductive coil portion.

15. (Original) A counteracting magnetic field generator according to Claim 12 wherein the windings comprise end windings extending outwardly beyond respective ends of the stator core; and wherein said second electrically conductive coil portion is positioned adjacent at least one end winding.

16. (Original) A counteracting magnetic field generator according to Claim 12 wherein relative positioning of said first and second electrically conductive coil portions provides a desired phase offset for the counteracting magnetic field.

17. (Original) A counteracting magnetic field generator for a power generator comprising a rotor and a stator surrounding the rotor and having opposing ends, the stator comprising a stator core and a plurality of windings carried by the stator core creating an undesired axial magnetic field component adjacent the opposing ends of the stator, the counteracting magnetic field generator generating a counteracting magnetic field for counteracting the undesired

In re Patent Application of
LEONOV

Serial No. 10/728,691

Filed: DECEMBER 5, 2003

BEST AVAILABLE COPY

axial magnetic field component at at least one end of the stator and comprising:

an electrically conductive coil portion adjacent an end of the stator; and

a power source connected to said electrically conductive coil portion to generate the counteracting magnetic field.

18. (Original) A counteracting magnetic field generator according to Claim 17 further comprising at least one magnetic field sensor; and wherein said power source comprises a controller for controlling the counteracting magnetic field based upon said at least one magnetic field sensor.

19. (Original) A counteracting magnetic field generator according to Claim 17 wherein said power source provides a desired phase offset for the counteracting magnetic field.

20. (Currently amended) A method for counteracting an undesired axial magnetic field component adjacent at least one end of a stator surrounding a rotor, the undesired axial magnetic field component created by a plurality of windings carried by a stator core of the stator, the method comprising:
generating a counteracting magnetic field adjacent the at least one end of the stator to counteract the undesired axial magnetic field component;

In re Patent Application of
LEONOV
Serial No. 10/728,691
Filed: DECEMBER 5, 2003

BEST AVAILABLE COPY

inducing an electrical current in a first
electrically conductive coil portion;

connecting a second electrically conductive coil
portion to the first electrically conductive coil portion to
receive the electrical current therefrom to generate the
counteracting magnetic field; and

positioning the second electrically conductive coil
portion adjacent the at least one end of the stator.

21. (Canceled).

22. (Currently amended) A method according to
Claim 20 [[21]] further comprising positioning the first
electrically conductive coil in a gap between the stator and
the rotor.

23. (Currently amended) A method according to
Claim 20 [[21]] further comprising positioning the first
electrically conductive coil portion in a recess in the stator
core.

24. (Currently amended) A method according to
Claim 20 [[21]] wherein the windings comprise end windings;
and further comprising positioning the second electrically
conductive coil portion adjacent at least one end winding.

25. (Currently amended) A method according to
Claim 20 [[21]] wherein relative positioning of the first and

In re Patent Application of
LEONOV

Serial No. 10/728,691

Filed: DECEMBER 5, 2003

BEST AVAILABLE COPY

second electrically conductive coil portions provides a desired phase offset for the counteracting magnetic field.

Claims 26-28 (Canceled).

29. (New) A method for counteracting an undesired axial magnetic field component adjacent at least one end of a stator surrounding a rotor, the undesired axial magnetic field component created by a plurality of windings carried by a stator core of the stator, the method comprising:

generating a counteracting magnetic field adjacent the at least one end of the stator to counteract the undesired axial magnetic field component;

positioning an electrically conductive coil portion adjacent and end of the stator; and

connecting a power source to the electrically conductive coil to generate the counteracting magnetic field.

30. (New) A method according to Claim 29 further comprising controlling the counteracting magnetic field based upon at least one magnetic field sensor.

31. (New) A method according to Claim 29 wherein the power source provides a desired phase offset for the counteracting magnetic field.